



MINIECLIPSE TR

Track mounted mini LED profile with knob-dimming



LIGHT SOURCE

1x28W
CREE LED



BEAM ANGLE

19° / 26° /
36° / 50° optional



CONNECTIVITY

track adaptor
(EUTRAC, STAFF,
GLOBAL, IVELA
compatible)



IP RATING

20

MINIECLIPSE TR is the track-mounted version of MINIECLIPSE LED ellipsoidal, featuring the elegant white housing proving it's worth as an innovative and perfect solution for installation in commercials, showrooms, museums and churches.

It showcases a stylish design, ease of use, precise optics, sharp image projection and bright flat projection all in a compact housing thus keeping superior brightness and high CRI white reproduction.

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

- Source: 1x28W CREE LED
- CT: TU 3100 K - DY 6000K
- CRI: TU 93 - DY 91
- Luminous flux: TU 612 lm - DY 700lm
- Lux: TU 880 lux - DY 1037lux @3m - 19°

OPTICS

- Beam angle: optional 19° / 26° / 36° / 50°
- Lens type: high-quality glass lens optics

DYNAMIC EFFECTS

- Fixed gobos: Gobo Holder Included in optics

ELECTRONICS

- Dimmer: linear 0~100%, manual knob dimmer

ELECTRICAL

- Power consumption (at 230V): 29W

PHYSICAL

- Power connection: moulded IP power IN connector
- IP rating: 20
- Dimensions (WxHxD): 112x210x226mm
- Weight: 1.2kg

FEATURES

- Track mounted compact LED ellipsoidal with sharp optics.
- Available with warm and cool white high CRI LED sources.
- 19°, 26°, 36° and 50° lens options.

Variants



MINIECLIPSE TR TU
WarmWhite LED source,



MINIECLIPSE TR WDTU
WarmWhite LED source, DMX



MINIECLIPSE TR DY
ColdWhite LED source,



MINIECLIPSE TR WDDY
ColdWhite LED source, DMX