

Datasheet

Title: LED Emergency Twin Spot



Features

- Ideal replacement for old style halogen twin spot fittings
- Fitting incorporates LED indicators and built in sounder to show lamp status and alert of faults
- White output (3500K)
- Tilt and pan heads allows light to be directed as required
- Durable polycarbonate body
- 3 hour emergency duration
- 3 year guarantee

Standards

- EN 60598-1: 2008+A11: 2009
- EN 60598-2-22: 1998+A1: 2003+A2: 2008
- EN 55015: 2013
- EN 61000-3-2: 2006+A2: 2009
- EN 61000-3-3: 2013
- EN 61547: 2009

Range

LED 7.5W Emergency Twin Spot 795-9381

Dimensions

	795-9381
Length	296mm
Height	272mm
Depth	75mm

Technical Specification

Voltage (driver)	230V~ 50Hz
Lamp type	2x15 pcs SMD2835 3500K
Colour temp.	
Lamp Wattage	2x7.5W
Lumen Output	470lm
Emergency duration	3 hours minimum
Battery	9.6V 2.2Ah NiCd
IP Rating	IP65

Spacing Tables

Mounting height	Transverse to wall	Transverse to transverse
2.5m	3.0	10.0
4.0m	4.0	11.0
6.0m	4.0	12.0
8.0m	4.5	13.0

All spacings are calculated to achieve 1 lux minimum