



**Una nueva clase de cámara PTZ con 4K 50p que abre nuevas posibilidades en la producción audiovisual.**

## AW-UE150

La AW-UE150 será la última incorporación a la completa gama de cámaras PTZ profesionales de Panasonic. Con un sensor MOS de tipo 1, esta cámara PTZ de última generación es compatible con vídeo 4K 50p de alta calidad, cuenta con un ángulo de visualización de 75,1 grados, zoom óptico de 20x y es compatible con salidas versátiles, que incluyen 12G-SDI, HDMI, fibra óptica e IP. El funcionamiento simultáneo en 4K/HD convierte a esta cámara PTZ en ideal para todos aquellos que buscan un sistema pensado para el futuro.

### Key Features

Primera cámara PTZ integrada 4K 50p

Ángulo de visualización horizontal de 75,1° (el más amplio de su categoría)

Varias interfaces 4K (12G-SDI, HDMI, fibra óptica, IP)

Zoom óptico de 20x + iZoom

Salida simultánea 4K/HD



PROFESSIONAL PARTNER LEVEL PROFESSIONAL PARTNER LEVEL



**BOSCH**



**BOSCH**





## AW-UE150

<https://eu.connect.panasonic.com/es/es/broadcast-proav/remote-ptz-camera-systems/aw-ue150>

|                                                          |                                                                                                                                                                                              |
|----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General -> Power Requirements                            | 12 V DC (10.8 V to 13.2 V), DC 42 V to 57 V (Camera Input, PoE++ power supply)                                                                                                               |
| General -> Current Consumption                           | 4.0 A (XLR IN connector), 1.2 A (PoE++ power supply)                                                                                                                                         |
| General -> Ambient Operating Temperature                 | 0 °C to 40 °C (32 °F to 104 °F)                                                                                                                                                              |
| General -> Ambient Operating Humidity                    | 0 °C to 40 °C (32 °F to 104 °F)                                                                                                                                                              |
| General -> Storage Temperature                           | -20 °C to 50 °C (-4 °F to 122 °F)                                                                                                                                                            |
| General -> Weight                                        | Approx. 4.2 kg (9.24 lb) (excluding mount bracket)                                                                                                                                           |
| General -> Dimensions                                    | W 213 mm x H 267 mm x D 219 mm<br>(8-3/8 inches x 10-1/2 inches x 8-5/8 inches)<br>(excluding protrusions, direct ceiling mount bracket)                                                     |
| General -> Finish                                        | AW-UE150WP/AW-UE150WE: Pearl white<br>AW-UE150KP/AW-UE150KE: Black                                                                                                                           |
| General -> Controller Supported *1                       | See the "Compatibility Chart for Operation Devices and Application Software" page                                                                                                            |
| Camera Unit -> Imaging Sensor                            | 1-type 4K MOSx1                                                                                                                                                                              |
| Camera Unit -> Effective Pixels                          | 20,180,000 pixel                                                                                                                                                                             |
| Camera Unit -> Zoom                                      | • Optical zoom: 20x<br>• i.Zoom: UHD 24x, FHD 32x<br>• Digital zoom: 10x                                                                                                                     |
| Camera Unit -> Lens                                      | Motorized Optical 20x zoom, F2.8 to F4.5<br>[f=8.8 mm (1 1/32 inches) to 176.0 mm (6-15/16 inches);<br>35 mm (1-3/8 inches) equivalent: 24.5 mm (31/32 inches) to 490.0 mm (19-9/32 inches)] |
| Camera Unit -> Conversion Lens                           | Not supported                                                                                                                                                                                |
| Camera Unit -> Angle of View Range                       | Horizontal angle of view: 75.1° (wide) to 4.0° (tele)<br>Vertical angle of view: 46.7° (wide) to 2.3° (tele)<br>Diagonal angle of view: 82.8° (wide) to 4.6° (tele)                          |
| Camera Unit -> Optical Filter -> ND Filter               | Through, 1/4, 1/16, 1/64, IR through (IR through is used as "Night mode")                                                                                                                    |
| Camera Unit -> Focus                                     | Switching between auto and manual                                                                                                                                                            |
| Camera Unit -> Focus Distance                            | Entire zooming range: 1000 mm (3.3 ft)<br>Wide end: 100 mm (0.33 ft)                                                                                                                         |
| Camera Unit -> Color Separation Optical System           | 1MOS                                                                                                                                                                                         |
| Camera Unit -> Standard Sensitivity                      | F9, 2000 lx (When normal mode is selected)                                                                                                                                                   |
| Camera Unit -> Minimum Illumination                      | 2 lx (F2.8, 59.94p, 50IRE, 42 dB, without accumulation)                                                                                                                                      |
| Camera Unit                                              | 60 dB or more                                                                                                                                                                                |
| Camera Unit -> Horizontal Resolution                     | > 4K<br>-2,000 TV lines Typ (Center area)                                                                                                                                                    |
| Camera Unit -> Gain Selection                            | Auto, -3 dB to 36 dB *2<br>Super Gain function equipped : +37 dB to 42 dB                                                                                                                    |
| Camera Unit -> Frame Mix *3                              | 0 dB, 6 dB, 12 dB, 18 dB, 24 dB                                                                                                                                                              |
| Camera Unit -> Electronic Shutter Speed -> 59.94p/59.94i | 1/60, 1/100, 1/120, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/8000, 1/10000                                                                                                                    |
| Camera Unit -> Electronic Shutter Speed -> 50p/50i       | 1/60, 1/100, 1/120, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/8000, 1/10000                                                                                                                    |
| Camera Unit -> Electronic Shutter Speed -> 29.97p        | 1/30, 1/60, 1/100, 1/120, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/8000, 1/10000                                                                                                              |
| Camera Unit -> Electronic Shutter Speed -> 25p           | 1/25, 1/50, 1/60, 1/100, 1/120, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/8000, 1/10000                                                                                                        |
| Camera Unit -> Electronic Shutter Speed -> 23.98p/24p    | 1/24, 1/48, 1/60, 1/100, 1/120, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/8000, 1/10000                                                                                                        |
| Camera Unit -> Synchro Scan -> 59.94p/59.94i             | 60.00 Hz to 7200 Hz                                                                                                                                                                          |
| Camera Unit -> Synchro Scan -> 50p/50i                   | 50.00 Hz to 7200 Hz                                                                                                                                                                          |
| Camera Unit -> Synchro Scan -> 29.97p                    | 30.00 Hz to 7200 Hz                                                                                                                                                                          |
| Camera Unit -> Synchro Scan -> 25p                       | 25.00 Hz to 7200 Hz                                                                                                                                                                          |
| Camera Unit -> Synchro Scan -> 23.98p/24p                | 24.00 Hz to 7200 Hz                                                                                                                                                                          |
| Camera Unit -> Gamma                                     | HD / FILMLIKE1 / FILMLIKE2 / FILMLIKE3 / FILM REC / VIDEO REC / HLG                                                                                                                          |
| Camera Unit -> White Balance                             | ATW : 3200K, 5600K<br>ATW Speed : Normal / Slow / Fast<br>AWB : AWB-A / AWB-B<br>VAR (selectable between 2000K and 15000K by designating a value)                                            |
| Camera Unit -> Chroma Amount Variability                 | OFF, -99 % to 99 %                                                                                                                                                                           |
| Camera Unit -> Scene File                                | Scene1, Scene2, Scene3, Scene4                                                                                                                                                               |

|                                                                                      |                                                                                                                                                                                                                                                                                                                                                                              |
|--------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Camera Unit -&gt; Output Format (SDI) -&gt; 4K</b>                                | 2160/59.94p, 2160/50p, 2160/29.97p *4, 2160/25p *4, 2160/24p *4, 2160/23.98p *4                                                                                                                                                                                                                                                                                              |
| <b>Camera Unit -&gt; Output Format (SDI) -&gt; HD</b>                                | 1080/59.94p, 1080/50p, 1080/29.97p *4, 1080/29.97PsF, 1080/25p *4, 1080/25PsF, 1080/23.98p *5, 1080/24p *4, 1080/23.98p *4, 1080/23.98PsF, 1080/59.94i, 1080/50i, 720/59.94p, 720/50p                                                                                                                                                                                        |
| <b>Camera Unit -&gt; Output Format (HDMI) -&gt; 4K</b>                               | 2160/59.94p, 2160/50p, 2160/29.97p *4, 2160/25p *4, 2160/24p *4, 2160/23.98p *4                                                                                                                                                                                                                                                                                              |
| <b>Camera Unit -&gt; Output Format (HDMI) -&gt; HD</b>                               | 1080/59.94p, 1080/50p, 1080/29.97p *4, 1080/29.97PsF, 1080/25p *4, 1080/25PsF, 1080/23.98p, 1080/24p *4, 1080/23.98p *4 *5, 1080/23.98PsF, 1080/59.94i, 1080/50i, 720/59.94p, 720/50p                                                                                                                                                                                        |
| <b>Camera Unit -&gt; Output Format(Fiber (video only)) -&gt; 4K</b>                  | 2160/59.94p, 2160/50p, 2160/29.97p, 2160/25p, 2160/24p, 2160/23.98p                                                                                                                                                                                                                                                                                                          |
| <b>Camera Unit -&gt; Output Format(Fiber (video only)) -&gt; HD</b>                  | 1080/59.94p, 1080/50p, 1080/29.97p, 1080/29.97PsF, 1080/25p, 1080/25PsF, 1080/23.98p, 1080/24p, 1080/23.98p, 1080/23.98PsF, 1080/59.94i, 1080/50i, 720/59.94p, 720/50p                                                                                                                                                                                                       |
| <b>Synchronization System</b>                                                        | Internal/External synchronization (BBS/Tri-level sync)                                                                                                                                                                                                                                                                                                                       |
| <b>Input Connector -&gt; DC IN</b>                                                   | DC 12 V IN                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Input Connector -&gt; G/L IN</b>                                                  | BBS (Black Burst Sync), tri-level sync supported                                                                                                                                                                                                                                                                                                                             |
| <b>Output Connector -&gt; HDMI</b>                                                   | HDMI 2.0 standard<br>4:2:2/10bit<br>• HDCP is not supported.<br>• Viera Link is not supported.                                                                                                                                                                                                                                                                               |
| <b>Output Connector -&gt; 12G-SDI OUT</b>                                            | SMPTE 2082-1 standard / 75 Ω (BNC x 1)                                                                                                                                                                                                                                                                                                                                       |
| <b>Output Connector -&gt; 3G-SDI OUT</b>                                             | SMPTE424M/SMPTE292 / 75 Ω (BNC x 1)<br>• Level-A/Level-B supported                                                                                                                                                                                                                                                                                                           |
| <b>Output Connector -&gt; MONIOUT</b>                                                | SMPTE292 / 75 Ω (BNC x 1)                                                                                                                                                                                                                                                                                                                                                    |
| <b>Output Connector -&gt; OpticalFiber</b>                                           | SFP+ standard<br>• This unit does not support input by optical signals                                                                                                                                                                                                                                                                                                       |
| <b>Input/Output Connector -&gt; LAN</b>                                              | LAN connector for IP control (RJ-45) 100BASE-TX/1000BASE-T                                                                                                                                                                                                                                                                                                                   |
| <b>Input/Output Connector -&gt; RS-422</b>                                           | CONTROL IN RS-422A (RJ-45)                                                                                                                                                                                                                                                                                                                                                   |
| <b>Input/Output Connector -&gt; MIC/LINE Input</b>                                   | AAC compatible (compatible with IP only)<br>ø 3.5 mm stereo mini jack<br>Input impedance: High impedance<br>• During MIC input<br>Supported mic: Stereo mic (plug-in power, on/off switching via menu)<br>Supply voltage: 2.5 V ± 0.5 V<br>Mic input sensitivity: Approx. -40 dBV ± 3 dBV (0 dB=1 V/Pa, 1 kHz)<br>• During LINE input<br>Input level: Approx. -10 dBV ±3 dBV |
| <b>Pan-tilt Head Unit -&gt; IP connecting cable</b>                                  | LAN cable *6 *7: (category 5e or above, straight cable / crossover cable), max. 100 m (328 ft)                                                                                                                                                                                                                                                                               |
| <b>Pan-tilt Head Unit -&gt; AW protocol connecting cable</b>                         | LAN cable *6: (category 5e or above, straight cable), max. 1000 m (3280 ft)                                                                                                                                                                                                                                                                                                  |
| <b>Pan-tilt Head Unit -&gt; Installation Method</b>                                  | Stand-alone (Desktop) or suspended (Hanging) *8                                                                                                                                                                                                                                                                                                                              |
| <b>Pan-tilt Head Unit -&gt; Pan/tilt Operation Speed</b>                             | Minimum speed 0.08°/s<br>Maximum speed 60°/s or higher *9<br>• Maximum speed is 180°/s in high-speed mode                                                                                                                                                                                                                                                                    |
| <b>Pan-tilt Head Unit -&gt; Panning Range</b>                                        | ±175°                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Pan-tilt Head Unit -&gt; Tilting range</b>                                        | -30° to 210° *10                                                                                                                                                                                                                                                                                                                                                             |
| <b>Pan-tilt Head Unit -&gt; Quietness</b>                                            | NC35 or less                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Supported Operating Systems and Web Browsers -&gt; Windows *11</b>                | Microsoft® Windows® 7, 10 Windows® Internet Explorer® 11 (64-bit/32-bit)<br>Microsoft Edge Google Chrome                                                                                                                                                                                                                                                                     |
| <b>Supported Operating Systems and Web Browsers -&gt; Mac *11</b>                    | Mac OS 10.13, Mac OS 10.12, Mac OS 10.11<br>Safari 11, Google Chrome                                                                                                                                                                                                                                                                                                         |
| <b>Supported Operating Systems and Web Browsers -&gt; iPhone/iPad *11</b>            | iOS 11.4.1<br>Google Chrome                                                                                                                                                                                                                                                                                                                                                  |
| <b>IP Streaming -&gt; Image Streaming Mode</b>                                       | JPEG (MJPEG), H.264, H.265                                                                                                                                                                                                                                                                                                                                                   |
| <b>IP Streaming -&gt; Image Resolution</b>                                           | 3840x2160, 1920x1080, 1280x720, 640x360, 320x180                                                                                                                                                                                                                                                                                                                             |
| <b>IP Streaming -&gt; Image Transmission Setting (JPEG)</b>                          | Frame Rate: Maximum 30 fps<br>Image quality (Fine / Normal)                                                                                                                                                                                                                                                                                                                  |
| <b>IP Streaming -&gt; Image Transmission Setting (H.264) -&gt; Transmission Type</b> | Unicast port (AUTO)<br>Unicast port (MANUAL)<br>Multicast port                                                                                                                                                                                                                                                                                                               |
| <b>IP Streaming -&gt; Image Transmission Setting (H.264) -&gt; Transmission mode</b> | Constant bit rate<br>Frame rate<br>Best effort                                                                                                                                                                                                                                                                                                                               |
| <b>IP Streaming -&gt; Image Transmission Setting (H.264) -&gt; Frame Rate</b>        | [60Hz] 5fps / 15fps / 30fps / 60fps (UHD: 30fps, 60fps)<br>[50Hz] 5fps / 12.5fps / 25fps / 50fps (UHD: 25fps, 50fps)                                                                                                                                                                                                                                                         |
| <b>IP Streaming -&gt; Image Transmission Setting (H.264) -&gt; Max Bit Rate</b>      | HD:<br>512kbps / 768kbps / 1024kbps / 1536kbps / 2048kbps / 3072kbps / 4096kbps / 6144kbps /<br>8192kbps / 10240kbps / 12288kbps / 14336kbps / 16384kbps / 20480kbps / 24576kbps /<br>32768kbps / 40960kbps / 51200kbps / 76800kbps<br>UHD:<br>12800kbps / 25600kbps / 51700kbps / 76800kbps                                                                                 |
| <b>IP Streaming -&gt; Image Transmission Setting (H.265) -&gt; Transmission Type</b> | Unicast port (AUTO)<br>Unicast port (MANUAL)<br>Multicast port                                                                                                                                                                                                                                                                                                               |
| <b>IP Streaming -&gt; Image Transmission Setting (H.265) -&gt; Frame Rate</b>        | [60Hz] 30fps<br>[50Hz] 25fps                                                                                                                                                                                                                                                                                                                                                 |
| <b>IP Streaming -&gt; Image Transmission Setting (H.265) -&gt; Max Bit Rate</b>      | 8192kbps / 12800kbps / 25600kbps / 51200kbps / 76800kbps                                                                                                                                                                                                                                                                                                                     |

|                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>IP Streaming -&gt; Audio Compression Format</b>      | AAC-LC, 48 kHz / 16 bit / 2ch                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>IP Streaming -&gt; Supported Protocol -&gt; IPv6</b> | TCP / IP, UDP / IP, HTTP, HTTPS, DNS, NTP, DHCPv6, RTP, MLD, ICMP, ARP, RTMP, SRT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>IP Streaming -&gt; Supported Protocol -&gt; IPv4</b> | TCP / IP, UDP / IP, HTTP, HTTPS, RTSP, RTP / RTCP, DHCP, DNS, DDNS, NTP, UPnP, IGMP, ICMP, ARP, RTMP, RTMPS, SRT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>NDI® Support -&gt; NDI® Support</b>                  | NDI® HX version 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Other Function -&gt; Tally LED Display Color</b>     | red / green                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Nota a pie de página</b>                             | <p>* NDI® is a registered trademark of Vizrt NDI AB in the United States and other countries.</p> <ol style="list-style-type: none"> <li>1. Use may require a software version update.</li> <li>2. 1 dB step increments can be set.</li> <li>3. This cannot be configured when the format is 2160/29.97p, 2160/23.98p, 2160/24p, 2160/25p, 1080/29.97p, 1080/23.98p(59.94i), 1080/29.97PsF, 1080/23.98PsF, 1080/25p, 1080/25PsF.</li> <li>4. Native output.</li> <li>5. It denotes "1080/23.98p over 59.94i".</li> <li>6. Use of an STP (shielded twisted pair) cable is recommended.</li> <li>7. Category 6 or more is used when sending 4K images.</li> <li>8. To ensure safety, the unit must be secured using the mount bracket supplied.</li> <li>9. Quietness, stationary accuracy, etc., in high-speed mode may vary from normal mode.</li> <li>10. Depending on the pan or tilt position, the camera may be reflected in the image.</li> <li>11. Supported OS indicated are for browsers current as of October 2018. See Service and Support for the latest information on browser support.</li> <li>12. Contact your local Panasonic vendor for further information.</li> </ol> |